

## ProSet® XT3 - The High Performer



**76003-00001** - The ProSet XT3 can be used in a variety of applications, setting a large range of breakstem rivets, lockbolts and sealing plug sizes. The extremely large stroke of 26 mm allows the placement of longer rivets like Monobolt and Interlock in one set.

The robust tool rubber base is designed to avoid damage. Latest technology lip seals maximise re-priming intervals. Piston bearing rings ensure maximum robustness and tool life.

### Specifications

Weight, incl. nose equipment	2.14 kg
Weight, without nose equipment	2.0 kg
Pull force at 5.5 bar	17.0 kN
Force/Weight ratio	7.94 kN/kg
Stroke (min.)	26 mm
Cycle time (approximate)	0.9 sec
Air supply pressure (dry, filtered)	5.0 - 7.0 bar
Free air volume at 5.5 bar	6.3 l
Noise level	78.4 dB(A)

## ProSet® XT4 - The Powerful



**76004-00001** - The ProSet XT4 is the strongest tool of the ProSet family. With 23 kN the XT4 delivers the highest pull force in the range but weighs in at just about 2 kg. Beside structural breakstem rivets, the high capacity of the XT4 also allows to install Avdelok, Maxlok and Avtainer lockbolts. The tool features an ultra-high tensile piston rod for maximum tool life and a hydraulic damping for smooth operation.

The robust tool rubber base is designed to avoid damage. Latest technology lip seals maximise re-priming intervals. Piston bearing rings ensure maximum robustness and tool life.

### Specifications

Weight, incl. nose equipment	2.16 kg
Weight, without nose equipment	2.0 kg
Pull force at 5.5 bar	23.0 kN
Force/Weight ratio	10.65 kN/kg
Stroke (min.)	18 mm
Cycle time (approximate)	1.0 sec
Air supply pressure (dry, filtered)	5.0 - 7.0 bar
Free air volume at 5.5 bar	6.3 l
Noise level	77.9 dB(A)

**STANLEY**  
Engineered Fastening

[stanleyengineeredfastening.com](http://stanleyengineeredfastening.com)

© 2017 Stanley Black & Decker, Inc., Rev. 11.2017

STANLEY Engineered Fastening  
Avdel UK Limited  
Stanley House, Works Road  
Letchworth Garden City  
Hertfordshire SG6 1JY, UK  
Tel. +44 (0)1582 900 000  
Fax. +44 (0)1582 900 001  
[enquiries2@sbdinc.com](mailto:enquiries2@sbdinc.com)

STANLEY Engineered Fastening  
Emhart Teknologies B.V.  
P.O. Box 70  
6120 AB Born  
The Netherlands  
Tel. +31 (0)43 750 2000  
Fax. +31 (0)43 750 2030  
[PopAvdel@sbdinc.com](mailto:PopAvdel@sbdinc.com)